	Model: 16M33G6N0/5	Date: 7/1/2020
	PowerKit Gas Engine Datasheet	


Ratings

	1500 rpm / 50 Hz		
	COP kWm	PRP kWm	ESP kWm
Gross Engine Power	1280	N/A	N/A
Net Engine Power	TBD	N/A	N/A

Basic data

Engine model	16M33G6N0/5
N° of Cylinders / Valves	16 / 64
Cylinders arrangement	V-engine
Bore x Stroke (mm)	150 x 185
Displacement (L)	52.3
Mean Piston Speed (m/s)	9.25
BMEP (Bar)	19.6
Fuel	Pipeline Natural Gas - MN \geq 88
Cooling System	Liquid (water + 50% antifreeze)
Injection System	Open Chamber
Fuel System	Lean Burn Spark Ignited
Aspiration	Turbocharged and Aftercooled
Compression ratio	12.5 : 1
Flywheel housing	SAE 0
Flywheel	18"
N° of teeth on flywheel ring gear	194
Inertia of flywheel (kg/m ²)	7.2
Inertia of crankshaft (kg/m ²)	10.1
Emission	N/A
Overall Dimensions without radiator (Length x Width x Height) (mm)	2781 x 1564 x 1881
Engine dry weight (without radiator) (kg)	5300
Engine wet weight (includes oil, coolant) (kg)	6060
Max ambient temperature restriction (°C) ¹	40

¹ The indicated value is based on an AOT value of 50°C for an engine tested at 100% of the COP Power, in an open condition, without an enclosure or container, without any airflow obstruction in the front of the radiator, without air recirculation, with free exhaust gas exit and with the engine thermostatic valve in its full open condition, without a closing plate present.

	Model: 16M33G6N0/5	Date: 7/1/2020
	PowerKit Gas Engine Datasheet	

Air intake system

Max temperature rise before turbocharger (°C)	≤ 2
Air intake restriction clean filter (mBar)	≤ 15
Air intake restriction dirty filter (mBar)	≤ 25
Recommended air flow Volume / Mass @ COP (m ³ /min) / (Kg/h)	84.9 / 6034
Recommended air flow Volume / Mass @ PRP (m ³ /min) / (Kg/h).....	N/A / N/A
Recommended air flow Volume / Mass @ ESP (m ³ /min) / (Kg/h)	N/A / N/A

Intercooling system


Intercooler heat dissipating capacity @ COP (KW)	311.4
Intercooler heat dissipating capacity @ PRP (KW)	N/A
Intercooler heat dissipating capacity @ ESP (KW)	N/A
Max. intake temperature @ 25°C ambient temperature (°C)	55
Max. difference between intake temperature and ambient temperature (°C)	5
Max. intake pressure drop of intercooler (mBar).....	30

Cooling system

Min. inside diameter of coolant outlet pipe HT / LT (mm)	100 / 84
Coolant capacity of radiator and pipes (L)	N/A
Coolant capacity of the engine HT / LT (L)	100 / 30
Coolant alarm and shutdown temperature (°C)	95 / 98
Thermostat opening temperature / fully open temperature (°C)	80 / 92
Min. pressure in cooling system (Bar)	0.5
Coolant flow at engine pump at 1500 Rpm (HT / LT in m ³ /h)	93 / 34
Maximum additional cooling circuit restriction (mBar)	500

Cooling fan

Type	N/A
Air flow (m ³ /min)	N/A
Power consumption (KW)	N/A
Max allow back pressure (mBar)	N/A

	Model: 16M33G6N0/5	Date: 7/1/2020
	PowerKit Gas Engine Datasheet	Page: 3 / 4

Exhaust system

Max. exhaust back pressure (mBar)	50
Min. exhaust back pressure (mBar)	0
Exhaust temperature after turbocharger (°C)	≤ 480
Exhaust flow Volume / Mass @ COP (m³/min) / (Kg/h)	292.7 / 6264
Exhaust flow Volume / Mass @ PRP (m³/min) / (Kg/h)	N/A / N/A
Exhaust flow Volume / Mass @ ESP (m³/min) / (Kg/h)	N/A / N/A
Min. diameter of exhaust pipe (mm)	240
Max. bending moment of exhaust gas exit flange (Nm)	10

Lubrication system

Oil capacity Low / High (L)	114 / 171
Oil pressure in normal condition idle speed (Bar)	≥ 2
Oil pressure in normal condition at 1500 Rpm @ PRP (Bar)	4 - 6.5
Lowest oil pressure alarm (shutdown) (Bar)	2
Highest oil pressure alarm (shutdown) (Bar)	10
Max. oil temperature (°C)	105
Oil flow (L/min)	≥ 533
Oil consumption at full load (g/kWhe-hr)	≤ 0.36
Total system capacity / including filters (L)	171 / 175

Noise

Engine sound pressure level (dB(A))@1m	101.1
Engine acoustic power level (dB(A))	118

Fuel system

Governor	ECU
Pressure loss from gas mixer (mBar)	N/A
Suction pressure max (mBar)	40
Max. Gas inlet temperature (°C)	50
Min / Max customer supply pressure before gas regulator (Bar)	0.3 / 0.5
Min / Max supply pressure at engine inlet (mBar)	40 / 70
Min. diameter of gas inlet pipe (mm)	80

Electrical system

Electrical system voltage (negative to ground) (Vdc)	24
Starter power (kW)	8.5
Battery charger current (A)	55
Max. electric resistance of starting circuit (mΩ)	8
Min. sectional area of wire (mm ²)	95
Min. cold start temperature without auxiliary starting device (°C)	0
Alternator battery charger consumption (KW).....	1.54

Heat balance test data (with ambient temperature 28 °C)

Load	COP			PRP		
	100%	75%	50%	100%	75%	50%
Total heat dissipation (KW)	1690.2	1300.94	939.6	N/A	N/A	N/A
Heat taken away by the coolant (KW)	560	447.7	369.9	N/A	N/A	N/A
Intercooler heat dissipating capacity (KW)	311.4	192	91.9	N/A	N/A	N/A
Available exhaust heat to 120 °C – (KW)	497.62	373.22	248.81	N/A	N/A	N/A
Radiated heat to ambient (KW)	152.8	118.2	83.8	N/A	N/A	N/A

Fuel consumption / Mechanical efficiency ISO3046/1

	COP			PRP	ESP
	100%	75%	50%	100%	100%
Full consumption LHV - (KW)	3056	2387	1675	N/A	N/A
Engine mechanical efficiency (%)	41.8	40.2	38.2	N/A	N/A
Fuel consumption tolerance + 5 %					

Ratings definitions

Emergency Standby Power (ESP)

Emergency Standby Power is the maximum power available for a varying load for the duration of a main power network failure. The average load factor over 24 hours of operation should not exceed 70% of the engine's ESP power rating. Typical operational hours of the engine is 200 hours per year, with a maximum usage of 500 hours per year. This includes an annual maximum of 25 hours per year at the ESP power rating. No overload capability is allowed. The engine is not to be used for sustained utility paralleling applications.

Prime Power (PRP)

Prime Power is the maximum power available for unlimited hours of usage in a variable load application. The average load factor should not exceed 70% of the engine's PRP power rating during any 24 hour period. An overload capability of 10% is available, however, this is limited to 1 hour within every 12 hour period.

Continuous Power (COP)

Continuous Power is the maximum power available for an unlimited period of use at a constant load factor. No overload capability is allowed.

- 1) All ratings are based on operating conditions under ISO 8528-1, ISO 3046, DIN6271. Performance tolerance of ±5%.
- 2) Test conditions : 100 kPa, 25°C air inlet temperature, relative humidity of 30%. Derating may be required for conditions outside these; please contact the factory for details.
- 3) Power output curves are based on the engine operating with fuel system, water pump and lubricating oil pump; not included are battery charging alternator, fan and optional equipment
- 4) The values given in this data sheet are for information purposes only and not binding